





טבלת התאמת מפתח לבורג ראש משושה (כולל טורק סגירה) מ"מ

12.9	10.9	-	8.8	4.6	MM	
0.31	0.26	-	0.18	0.07	3.2	M1.6
0.63	0.53	-	0.38	0.14	4	M2
1.31	1.09	-	0.78	0.29	5	M2.5
2.27	1.9	-	1.35	0.51	5.5	M3
4.29	3.57	-	2.54	0.95	7	M4
10.3	8.56	-	6.09	2.28	8	M5
17.7	14.7	-	10.5	3.92	10	M6
42.7	35.5	-	25.3	9.48	13	M8
85.8	71.5	-	50.8	19.1	17	M10
147	122	-	86.9	32.6	19	M12
234	195	-	139	52	22	M14
359	299	-	213	79.9	24	M16
495	413	-	293	110	27	M18
702	585	-	416	156	30	M20
950	792	-	563	211	32	M22
1213	1011	-	719	270	36	M24
1789	1491	-	1060	398	41	M27
2430	2025	-	1440	540	46	M30

3301	2751	-	1956	734	50	M33
------	------	---	------	-----	----	-----

המשך הטבלה:

12.9	10.9	-	8.8	4.6	MM	
4248	3540	-	2517	944	55	M36
5517	4597	-	3269	1226	60	M39
6832	5693	-	4049	1518	65	M42
8551	7126	-	5067	1900	70	M45
10296	8580	-	6101	2288	75	M48
13263	11052	-	7859	2947	80	M52
16425	13687	-	9733	3650	85	M56
20422	17018	-	12102	4538	90	M60
24597	20498	-	14576	5466	95	M64
29777	24814	-	17646	6617	100	M68

משך אספקה טכנית בע"מ - טלפון: 08-8519944, פקס: 08-8585445, רחוב האורג 12 מרכז עינב (ישפרו) מודיעין, מייל: sales@mashaf.co.il

